

OSREL ECOLUBE

Lubricant

Description

Osrel Ecolube is a ecologically friendly biodegradable vegetable based oil and is used to facilitate the easy jointing of concrete and clay pipes. **Osrel Ecolube** is supplied as a soft gel that is ready for direct application to the concrete surface, whether wet or dry.

Applications

Osrel Ecolube is used to lubricate concrete pipes, plastic or other sealing rings. It is immiscibly in water allowing it to be used in wet weather on site, it can also be used in wet and dry pipe jointing processes.

Benefits

- Biodegradable
- Excellent at low temperatures
- Immiscibly in water

Properties

Nature	Fluid Gel
Colour	Light Brown
Specific Gravity	0.96 g/cm ³
pH	-
Chloride Content	-
Na ₂ O equivalent	-

Instructions for use

Ensure that the concrete and surrounding areas are clean and free of contamination before the application of **Osrel Ecolube**.

Apply **Osrel Ecolube** around the entire circumference of the spigot and to the seal. Apply by brush, trowel sponge or gloved hand, to the desired area. re-apply to the spigot if the **Osrel Ecolube** becomes contaminated.

Standards

Osrel Ecolube is produced in accordance with the ISO 9001 Quality Management Standard and the ISO 14001 Environmental Management Standard.



OSREL ECOLUBE

Lubricant

Precautions

Osrel Ecolube is compatible with most 'O' ring gasket materials such as EPDM and neoprene. However, in case of any doubt please verify with Oscrete Technical Personnel.

Storage

Osrel Ecolube should be stored undercover and protected from extreme temperatures, if stored unopened within the range 5°C and 30°C the product will have a minimum shelf life of 6 months. Always re-seal container after use.

Handling

Please refer to the **Osrel Ecolube** Material Safety Data Sheet but in line with normal handling procedures, personal protective equipment should be worn.

Cleaning & Disposal

Equipment can be cleaning with detergent and warm, soapy water.

Please consult the OSCRETE Technical Department for advice on admixture selection.

Disclaimer

The physical properties quoted are typical, and should not be taken as a specification. The information supplied in our literature is based on data and experience and is given in good faith. Our policy is one of continuous research and development and we reserve the right to update this information at any time; customers should therefore ensure they have the latest issue. Whilst we guarantee the consistent high quality of our products, we have no control over the circumstances in which our materials are used, site conditions or the execution of the work and are therefore unable to accept any liability for any loss or damage which may arise as a result thereof. Materials are supplied in accordance with our standard conditions of sale.

OSCRETE is a division of Christeyns UK Ltd.
Rutland Street
Bradford
West Yorkshire
BD4 7EA
United Kingdom

Telephone: +44 (0)1274 393286

Fax: +44 (0)1274 309143

e-mail: info@oscrete.co.uk

Website: www.oscrete.co.uk

PDS 7384 Rev 03 18/01/2016

