

OSREL PROTECT

Surface Sealer/Protector

Description

Osrel Protect is a non-toxic silane based agent that provides an effective protective surface to repel oil, grease and other soiling materials.

Applications

Osrel Protect is a ready to use product and should be applied in a thin film, preferably on a dry surface. **Osrel Protect** is suitable for flagstones, cobbles, stone sets, paving blocks, permeable paving, slabs and concrete bricks.

Benefits

- Non-toxic
- UV stable
- Long lasting
- Easy to apply
- Stain repelling

Properties

Nature	Liquid
Colour	Opaque
Specific Gravity	1.00 g/cm ³
pH	7.0
Chloride Content	<0.10%
Na ₂ O equivalent	<1.00%

Addition Rates

1 litre will give a coverage rate of approx 7m²

Osrel Protect can be applied with a brush, roller or sprayer.

Standards

Osrel Protect is produced in accordance with the ISO 9001 Quality Management Standard and the ISO 14001 Environmental Management Standard.



OSREL PROTECT

Surface Sealer/Protector

Storage

Osrel Protect should be stored undercover and protected from extreme temperatures, if stored unopened within the range 5°C and 30°C the product will have a minimum shelf life of 12 months.

Handling

Please refer to the **Osrel Protect** Material Safety Data Sheet but in line with normal handling procedures, personal protective equipment should be worn.

Packaging

25 litre drums.

Notes

Preparation.

Ensure the surface is dry and clear of debris, dust or weeds. Apply in dry conditions.

Application.

By Hand: Pour sufficient product into a bucket. Using a sponge roller, apply evenly over the area to be covered. Allow to dry. Drying time vary but allow 2 hours to be touch dry and suitable for light foot traffic.

Spraying: Please ensure that **Osrel Protect** is applied evenly over the area to be treated.

Please consult the OSCRETE Technical Department for advice on admixture selection.

OSCRETE is a division of Christeyns UK Ltd.
Rutland Street
Bradford
West Yorkshire
BD4 7EA
United Kingdom

Telephone: +44 (0)1274 393286
Fax: +44 (0)1274 309143
e-mail: info@oscrete.co.uk
Website: www.oscrete.co.uk

PDS 7690 Rev 01 18/01/2016

Disclaimer

The physical properties quoted are typical, and should not be taken as a specification. The information supplied in our literature is based on data and experience and is given in good faith. Our policy is one of continuous research and development and we reserve the right to update this information at any time; customers should therefore ensure they have the latest issue. Whilst we guarantee the consistent high quality of our products, we have no control over the circumstances in which our materials are used, site conditions or the execution of the work and are therefore unable to accept any liability for any loss or damage which may arise as a result thereof. Materials are supplied in accordance with our standard conditions of sale.