

OSREL LEASE CA

High Performance Release Agent

PRODUCT DESCRIPTION

Osrel Lease CA is a chemical release agent specifically formulated to give easy release of formwork. The high performance surfactant blend provides excellent release properties whilst being economical and user friendly.

APPLICATIONS

Osrel Lease CA is particularly suitable for wood, metal, plastic and rubber moulds. **Osrel Lease CA** is supplied ready for use and should not be diluted, apply a thin and even coat to the clean formwork, care should be taken to avoid over application. For new and unsealed timber forms pre-treatment is recommended with a second application prior to use.

BENEFITS

- Quick and easy release of the formwork.
- Easy to apply by non-atomising spray, brush or roller.
- Suitable for wood, metal, plastic and rubber moulds.
- Low odour.
- Excellent surface finish.
- Suitable for heated beds.

PROPERTIES

Nature:	Liquid
Appearance:	Pale Yellow
Specific Gravity: (20°C)	0.84 g/cm ³
Viscosity: (cP @40°C)	9.0

ADDITION RATES

Coverage will depend on the type of mould or formwork and will be best determined by carrying out spraying trials prior to a full production run:

Typical coverage 30—40m² per litre

Osrel Lease CA can be applied with a brush, roller or a uniform thin film should be applied to the formwork using low pressure spray equipment. When using spray equipment allow for sufficient ventilation.

STANDARDS

Osrel Lease CA is produced in accordance with the ISO 9001 Quality Management Standard.



OSREL LEASE CA

High Performance Release Agent

COMPATIBILITY

Osrel Lease CA is compatible with all types of EN 197 cement systems and is compatible for use with all Oscrete admixtures.

STORAGE

Osrel Lease CA should be protected from extreme temperature, frost and direct sunlight, if stored unopened within the range 5°C—30°C the product will have a minimum shelf life of 12 months.

HANDLING

Please refer to the **Osrel Lease CA** material safety data sheet but in line with normal handling procedures, personal protective equipment should be worn.

PACKAGING

200 litres drums, 1000 litre IBC's and bulk deliveries.

NOTES

Osrel Lease CA will thicken at low temperatures, for this reason it is desirable to store the product in a frost free environment.

Please consult the OSCRETE technical department for advice on admixture selection.

Disclaimer

The physical properties quoted are typical, and should not be taken as a specification. The information supplied in our literature is based on data and experience and is given in good faith. Our policy is one of continuous research and development and we reserve the right to update this information at any time; customers should therefore ensure they have the latest issue. Whilst we guarantee the consistent high quality of our products, we have no control over the circumstances in which our materials are used, site conditions or the execution of the work and are therefore unable to accept any liability for any loss or damage which may arise as a result thereof. Materials are supplied in accordance with our standard conditions of sale.

OSCRETE is a division of Christeyns UK Ltd
Rutland Street
Bradford
West Yorkshire
BD4 7EA
United Kingdom

Telephone: +44 (0)1274 393286
Fax: +44 (0)1274 309143
E-mail: info@oscrete.com
Website: www.oscrete.com

PDS 8167 Rev 00 01/01/2020



OSCRETE
CONSTRUCTION PRODUCTS