

# OSREL TRUCK WASH

## Equipment Cleaner

### PRODUCT DESCRIPTION

**Osrel Truck Wash** is a specially formulated alternative to neat hydrochloric acid. It is designed to aid the removal and concrete and the build up associated with it on concrete trucks, mixers and equipment. **Osrel Truck Wash** also dramatically reduces the hazards associated with concentrated acids, such as burns and also reduce the risk of environmental damage.

### APPLICATIONS

**Osrel Truck Wash** is very effective in removing concrete deposits from vehicles concrete mixing equipment and civil engineering equipment.

### BENEFITS

- Classed only as an irritant.
- Replaces dangerous acids.
- Non-fuming.
- Out performs acids in speed of action.

### PROPERTIES

Nature:	Liquid
Appearance:	Opaque
Specific Gravity: (20°C)	1.07 g/cm <sup>3</sup>

### INSTRUCTIONS FOR USE

**Osrel Truck Wash** solution is best applied with a brush to provide a more concentrated point of attack on the concrete deposits. The strength of the solution may be varied, dependant on the amount of soiling and can safely be used at a 1-4 dilution with water or neat for very stubborn deposits. After leaving **Osrel Truck Wash** on the deposits for the appropriate time, it should be then vigorously brushed away using a stiff broom and water.

Note that the cleaning solution will gradually accumulate contaminants which will interfere with the performance. In order to prolong the performance life, it is recommended that **Osrel Truck Wash** be regularly applied to maintain the correct strength.

**Osrel Truck Wash** should always be added to the water already in the tank NOT the other way around, note, that **Osrel Truck Wash** is safe with all metals except zinc and aluminium.

### STANDARDS

**Osrel Expel** is produced in accordance with the ISO 9001 Quality Management Standard and the ISO 14001 Environmental Management Standard.



# OSREL TRUCK WASH

## Equipment Cleaner

### NOTES

The cleaning solution will gradually accumulate contaminants which will interfere with the performance. In order to prolong the performance life, it is recommended that a proportion be regularly discarded and strength maintained by necessary additions of **Osrel Truck Wash**.

### STORAGE

**Osrel Truck Wash** should be protected from extreme temperature, frost and direct sunlight, if stored unopened within the range 5°C—30°C the product will have a minimum shelf life of 12 months.

### HANDLING

Please refer to the **Osrel Truck Wash** material safety data sheet but in line with normal handling procedures, personal protective equipment should be worn.

### PACKAGING

25 litre drums, 200 litres drums, 1000 litre IBC's and bulk deliveries.

### CLEANING & DISPOSAL

Dilute with water if required, neutralisation may be done using soda ash or similar material.

Users should contact their local water authority to ascertain the requirements for disposing of this type of material. In its normal use as a concrete etcher or cleaner, little waste is generated. Residues will be washed off with water.

If disposal of a quantity of the product concentrate is required, the services of a suitable water disposal contractor should be used. Either wash away to effluent treatment with water, or absorb into a neutral medium such as sand. Earth or granules and bag off for disposal.

Please consult the OSCRETE technical department for advice on admixture selection.

OSCRETE is a division of Christeyns UK Ltd  
Rutland Street  
Bradford  
West Yorkshire  
BD4 7EA  
United Kingdom

#### Disclaimer

The physical properties quoted are typical, and should not be taken as a specification. The information supplied in our literature is based on data and experience and is given in good faith. Our policy is one of continuous research and development and we reserve the right to update this information at any time; customers should therefore ensure they have the latest issue. Whilst we guarantee the consistent high quality of our products, we have no control over the circumstances in which our materials are used, site conditions or the execution of the work and are therefore unable to accept any liability for any loss or damage which may arise as a result thereof. Materials are supplied in accordance with our standard conditions of sale.

Telephone: +44 (0)1274 393286  
Fax: +44 (0)1274 309143  
E-mail: [info@oscrete.com](mailto:info@oscrete.com)  
Website: [www.oscrete.com](http://www.oscrete.com)

PDS 7624 Rev 04 01/01/2020



**OSCRETE**  
CONSTRUCTION PRODUCTS