

For the product
OSCRETE 67/36
Product Code: **7787**

1. Unique identification code of the product type:

Oscrete 67/36 (7787)

2. Type, batch or serial number or any other identifying mark used to identify the construction product as set out in Article 11 (4):

Batch Number: Refer to Product Packaging

3. Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification:

Alkali Resistant Glass Fibre for Concrete

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in Article 11 (5):

European Owens Corning Fiberglass SPRL
Chaussée de la Hulpe, 166
1170 Watermael-Boitsfort
Belgium

5. When applicable, the name and contact address of the authorised representative who has received a mandate for the tasks set out in Article 12 (2):

Not applicable

6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V:

System 1

7. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard:

Not applicable

8. In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued:

UBAtc issued 17/0169 on the base of EAD 260002-00-0301

9. Declared performance

Essential Characteristics	Performance	Harmonised Technical Specification
Size content	2.0% by mass	ISO 1887
Average filament diameter	19µm	ISO 1888
Linear density	430 tex (g/1000m)	ISO 1889
Tensile strength of strands	> 1000 MPa > 700 MPa	ISO 3341 EN 14649
Alkali resistance (SIC Strength)	≥ 350 MPa	EN 14649
Effect on consistency of concrete	Reference concrete V3 (9 secs) Concrete with 20kg/m ² V3 (7 secs)	EN 14845-1
Effect on strength of concrete	For a dosage of 20kg/m ³ F (CMOD 0.5mm) = 3.0 MPa F (CMOD 3.5mm) = 1.4 MPa	EN 14845-2

10. The performance of the product identified in point 3 is in conformity with the declared performance set out in point 10.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for the manufacturer and in the name of the manufacturer by:



Dean Clarke
National Technical & Development Manager
Oscrete UK
Rutland Street
Bradford
West Yorkshire
BD4 7EA