



# DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulations (EU) No. 305/2011

Construction Products Regulation



For the product  
**OSPERSE PA20**  
Product Code: **7844**

1. Unique identification code of the product type:

**Osperse PA20 (7844)**

2. Type, batch or serial number or any other identifying mark used to identify the construction product as set out in Article 11 (4):

**Batch Number: Refer to Product Packaging**

3. Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification:

**Air Entraining Plasticising Admixture for Mortar**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in Article 11 (5):

**Christeyns UK Limited**  
**Rutland Street**  
**Bradford**  
**West Yorkshire**  
**BD4 7EA**  
**United Kingdom**

5. When applicable, the name and contact address of the authorised representative who has received a mandate for the tasks set out in Article 12 (2):

**Not applicable**

6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V:

**System 2+**

7. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard:

The notified body:

**DANCERT**  
*Identification Number*  
1073

Has carried out initial inspection of the factory and factory production control as well as continuous surveillance, assessment and evaluation of factory production Control to System 2+ and issued the following:

**Certificate of Factory Production Control**  
**No. 1073-CPR-7411**

8. In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued:

Not applicable

9. Declared performance

| Essential Characteristics                               | Performance                                                  | Harmonised Technical Specification |
|---------------------------------------------------------|--------------------------------------------------------------|------------------------------------|
| Chloride Content                                        | <0.10% by mass                                               | EN 934-3:2009 +A1:2012             |
| Alkali Content                                          | <2.00% by mass                                               | EN 934-3:2009+A1:2012              |
| Corrosion Behaviour                                     | Contains only components according to EN934-1:2008 Annex A.1 | EN 934-3:2009+A1:2012              |
| Air content after standard mixing                       | Total air content $A_1 = (17 \pm 3\%)$ by volume             | EN 934-3:2009+A1:2012              |
| Air content after 1 hour standing                       | $\geq A_1 - 3\%$                                             | EN 934-3:2009+A1:2012              |
| Air content after extended mixing                       | $\leq A_1 + 5\%$ and $\geq A_1 - 5\%$                        | EN 934-3:2009+A1:2012              |
| Reduction in water requirement for standard consistence | $\geq 8\%$ by mass                                           | EN 934-3:2009+A1:2012              |
| Compressive strength at 28 days                         | Test mix $\geq 70\%$ of control mix                          | EN 934-3:2009+A1:2012              |

When specific technical documentation in accordance with Articles 37 or 38 was used, the requirements that the product fulfils:

Not applicable

10. The performance of the product set out in numbers 1 and 2 corresponds to the declared performance set out in 9. The manufacturer as defined in number 4 is solely responsible for drawing up this declaration of performance.

Signed for the manufacturer and in the name of the manufacturer by:



Dean Clarke  
National Technical & Development Manager  
Oscrete Construction Products  
Rutland Street  
Bradford  
West Yorkshire  
BD4 7EA